



Technical data



	DAC 3000 HP	DAC 5000 HP	DAC 10000 HP
Mixing capacity min/max:	1500g ÷ 3000g	2500g ÷ 5000g	3500g ÷ 10000g
speed min/max:	50 ÷ 1000 rpm	50 ÷ 800 rpm	50 ÷ 800 rpm
mixing time min/max:	5s ÷ 600s	5s ÷ 600s	5s ÷ 600s
system voltage / frequency:	380V÷500V - 50/60 Hz	380V÷500V - 50/60 Hz	380V÷500V - 50/60 Hz
power rating:	4,0 KVA	4,0 KVA	7,0 KVA
height (lid closed):	1100 mm	1100 mm	1200 mm
height (lid open):	1540 mm	1540 mm	1800 mm
width:	1650 mm	1650 mm	1710 mm
depth:	1100 mm	1100 mm	1200 mm
weight:	1150 kg	1250 kg	1700 kg

Fixed and variable speed modes, 7.5" touchscreen display, unbalance sensor, key lock (OS), 20 programs, RS-232 interface.

DAC 3000 / 5000 / 10000 H-P



Hauschild & Co. KG

Waterkamp 1, 59075 Hamm, Germany
Phone +49 (0)2381 48205-0
Fax +49 (0)2381 48205-17
E-Mail info@speedmixer.de

www.speedmixer.de