



*SpeedMixer*TM

German Engineering
by Hauschild



DAC 150 / 250



Please scan
for more
information
about our
products.



Technical data

	DAC 150.1 FV	DAC 150.1 FV-K	DAC 150.1 FVZ	DAC 150.1 FVZ-K
mixing capacity min/max:	5-100g	5-100g	5-100g	5-100g
speed min/max:	300-3500 rpm	300-3500 rpm	300-3500 rpm	300-3500 rpm
mixing time min/max:	5s - 60 s - continuous	5s - 60 s - continuous	5s - 300 s - continuous	5s - 300 s - continuous
system voltage / frequency:	230 V / 50/60 Hz	230 V / 50/60 Hz	230 V / 50/60 Hz	230 V / 50/60 Hz
input power:	370 W	370 W	370 W	370 W
lid open - height:	630 mm	630 mm	630 mm	630 mm
width:	280 mm	280 mm	280 mm	280 mm
depth:	315 mm	315 mm	315 mm	315 mm
weight:	28 Kg	28 Kg	28 Kg	28 Kg

	DAC 150 SP	DAC 250 SP
mixing capacity min/max:	5-100g	5-150g
speed min/max:	300-3500 rpm	300-2500 rpm
mixing time min/max:	2s - 600 s - continuous	2s - 600 s - continuous
system voltage / frequency:	230 V / 50/60 Hz	230 V / 50/60 Hz
input power:	370 W	370 W
lid open - height:	650 mm	650 mm
width:	300 mm	300 mm
depth:	360 mm	360 mm
weight:	32 Kg	32 Kg



Your notes: